











Configurations and Pressure ratings for 32mm (1¼") Cocky Valves.

 150mm Arm (Float Above)	<i>For Plastic Troughs</i>	150mm (6") Float	200mm (8") Float	250mm(10")Float
	HP Pivot Point ONLY	Not Recommended	40 PSI (276kpa)	Not Recommended
 150mm Arm (Float on End)	<i>For Plastic Troughs</i>	150mm (6") Float	200mm (8") Float	250mm(10")Float
	HP Pivot Point ONLY	Not Recommended	90 PSI (621kpa)	Not Recommended
 300mm Arm (Float Above)	<i>Inlet below Water Line</i>	150mm (6") Float	200mm (8") Float	250mm(10")Float
	HP Pivot Point ONLY	35 PSI (241 kpa)	95 PSI (655kpa)	150PSI (1034kpa)
 300mm Arm (Float on End)	<i>Inlet on Water Line</i>	150mm (6") Float	200mm (8") Float	250mm(10")Float
	HP Pivot Point ONLY	50 PSI (345kpa)	125 PSI (862kpa)	150PSI (1034kpa)
 300mm Bent Arm (Float on End)	<i>Inlet above Water Line</i>	150mm (6") Float	200mm (8") Float	250mm(10")Float
	HP Pivot Point ONLY	50 PSI (345kpa)	125 PSI (862kpa)	150PSI (1034kpa)
 300mm Straight Arm (Float Above)	<i>Bottom Fill Troughs</i>	150mm (6") Float	200mm (8") Float	250mm(10")Float
	LP Pivot Point ONLY	25 PSI (172 kpa)	55 PSI (380kpa)	100PSI (690kpa)
 400mm Bent Arm (Float on End)	<i>Inlet on Water Line – (Mid-West Troughs)</i>	150mm (6") Float	200mm (8") Float	250mm(10")Float
	HP Pivot Point ONLY	50 PSI (345kpa)	125 PSI (862kpa)	150PSI (1034kpa)
 400mm Arm (Float Above)	<i>Inlet below Water Line</i>	150mm (6") Float	200mm (8") Float	250mm(10")Float
	LP Pivot Point	32 PSI (221 kpa)	70 PSI (483kpa)	150PSI (1034kpa)
	HP Pivot Point	50 PSI (345kpa)	105 PSI (724kpa)	150PSI (1034kpa)
 400mm Arm (Float on End)	<i>Inlet on Water Line</i>	150mm (6") Float	200mm (8") Float	250mm(10")Float
	LP Pivot Point	40 PSI (276 kpa)	100 PSI (689kpa)	150PSI (1034kpa)
	HP Pivot Point	65 PSI (448kpa)	130 PSI (896kpa)	150PSI (1034kpa)
 600mm Arm (Float Above)	<i>Inlet below Water Line</i>	150mm (6") Float	200mm (8") Float	250mm(10")Float
	LP Pivot Point	45 PSI (310kpa)	125 PSI (862kpa)	150PSI (1034kpa)
	HP Pivot Point	80 PSI (552kpa)	150PSI (1034kpa)	150PSI (1034kpa)

Whatever flow you get to your trough, you will get into your trough after fitting our valves.
There is NO REDUCTION in the flow rate.