











Configurations and Pressure ratings for 38mm (1½") Cocky Valves.

 <p>150mm Arm (Float Above)</p>	<i>For Plastic Troughs</i>	150mm (6") Float	200mm (8") Float	250mm(10")Float
	HP Pivot Point	Not Recommended	30 PSI (207kpa)	Not Recommended
 <p>150mm Arm (Float on End)</p>	<i>For Plastic Troughs</i>	150mm (6") Float	200mm (8") Float	250mm(10")Float
	HP Pivot Point	Not Recommended	60 PSI (414kpa)	Not Recommended
 <p>300mm Arm (Float Above)</p>	<i>Inlet below Water Line</i>	150mm (6") Float	200mm (8") Float	250mm(10")Float
	HP Pivot Point	25 PSI 172 kpa)	60 PSI (414kpa)	95 PSI (655kpa)
 <p>300mm Arm (Float on End)</p>	<i>Inlet on Water Line</i>	150mm (6") Float	200mm (8") Float	250mm(10")Float
	HP Pivot Point	35 PSI (241kpa)	100 PSI (689kpa)	150PSI (1034kpa)
 <p>300mm Bent Arm (Float on End)</p>	<i>Inlet above Water Line</i>	150mm (6") Float	200mm (8") Float	250mm(10")Float
	HP Pivot Point	35 PSI (241kpa)	100 PSI (689kpa)	150PSI (1034kpa)
 <p>300mm Straight Arm (Float Above)</p>	<i>Bottom Fill Troughs</i>	150mm (6") Float	200mm (8") Float	250mm(10")Float
	LP Pivot Point	15 PSI (103kpa)	30 PSI (207kpa)	70PSI (483kpa)
 <p>400mm Bent Arm (Float on End)</p>	<i>Inlet on Water Line – (Mid-West Troughs)</i>	150mm (6") Float	200mm (8") Float	250mm(10")Float
	HP Pivot Point	35 PSI (241kpa)	100 PSI (689kpa)	150PSI (1034kpa)
 <p>400mm Arm (Float Above)</p>	<i>Inlet below Water Line</i>	150mm (6") Float	200mm (8") Float	250mm(10")Float
	LP Pivot Point	22 PSI (152 kpa)	55 PSI (379kpa)	90 PSI (621kpa)
	HP Pivot Point	35 PSI (241kpa)	90 PSI (621kpa)	150PSI (1034kpa)
 <p>400mm Arm (Float on End)</p>	<i>Inlet on Water Line</i>	150mm (6") Float	200mm (8") Float	250mm(10")Float
	LP Pivot Point	25 PSI (172 kpa)	75 PSI (517kpa)	130 PSI (896kpa)
	HP Pivot Point	45 PSI (310kpa)	100 PSI (689kpa)	150PSI (1034kpa)
 <p>600mm Arm (Float Above)</p>	<i>Inlet below Water Line</i>	150mm (6") Float	200mm (8") Float	250mm(10")Float
	LP Pivot Point	Not Recommended	80 PSI (552kpa)	150PSI (1034kpa)
	HP Pivot Point	60 PSI (414kpa)	110 PSI (758kpa)	150PSI (1034kpa)

*Whatever flow you get to your trough, you will get into your trough after fitting our valves.
There is NO REDUCTION in the flow rate.*