



Cocky Valve Catalogue

Warehouse Address: **61 Macbeth St. Braeside Vic 3195**

Postal Address: **61 Macbeth St. Braeside Vic 3195**

Office Ph: **(03) 9798 2633** / Fax **(03) 9798 2422**

General Enquiries: **(Bernadette)** : Mob. **0409 002 013**

Technical Support: **(Peter)** : Mob. **0407 092 221**

Email: admin@cockyvalve.com.au

April 2018

VALVE BODIES

Valve Bodies

Our Valves are simply the best on the market for strength, performance and reliability. We offer a full replacement warranty against breakage when installed as recommended and used under normal operating conditions. Grade 316 Stainless Steel construction, Full Flow, in high or low-pressure applications and virtually indestructible by man or beast. Packet includes SS Body, 2 Split Pins, Push rod, washer and washer seat together with assembly instructions.

Available in the following sizes:













19mm (3/4"), 25mm (1"), 32mm (1 1/4"), 38mm (1 1/2"), 50mm (2")





	CODE	DESCRIPTION	BARCODE
	0007	19MM (3/4") S/STEEL VALVE BODY	 9 338862 000007
	0014	25MM (1") S/STEEL VALVE BODY	 9 338862 000014
	0021	32MM (1 1/4") S/STEEL VALVE BODY	 9 338862 000021
	0038	38MM (1 1/2") S/STEEL VALVE BODY	 9 338862 000038
	0380	50MM (2") S/STEEL VALVE BODY	 9 338862 000380

VALVE ARMS

Stainless steel arms.

We have a wide range of arms to suit a wide variety of trough types. In fact, we are confident that we can configure any trough to receive maximum in-flows at any pressure regardless of the trough constraints. Please refer to our DATA SHEETS and CONFIGURATION TABLES on our website for more detailed pressure ratings and recommendations.

	CODE	DESCRIPTION	BARCODE
	0625	THESE ARE OUR STANDARD ARMS 300MM LONG WITH AN M10 THREAD AT THE END – MATERIAL SS 316	 9 338862 000625
	0632	THESE ARE OUR STANDARD ARMS 400MM LONG WITH AN M10 THREAD AT THE END – MATERIAL SS 316	 9 338862 000632
	0649	THESE ARE OUR STANDARD ARMS 600MM LONG WITH AN M10 THREAD AT THE END – MATERIAL SS 316	 9 338862 000649
	0694	ARMS 300 M10 SS316 (100 THREAD). THESE ARMS WERE DEVELOPED FOR THE ROUND PLASTIC TROUGHS WHERE THERE ARE RESTRICTIVE CAVITIES FOR THE VALVES. THE THREAD CAN BE CUT BACK TO SUIT THE CAVITY.	 9 338862 000694
	0670	ARMS 400 M10 SS316 (BENT). THESE ARMS WERE DEVELOPED FOR THE MID WEST BRAND TROUGHS WHERE THERE ARE RESTRICTIVE CAVITIES FOR THE VALVES. THE FLOAT CAN BE ATTACHED DIRECTLY ONTO THE END OF THE ARM.	 9 338862 000670
	0663	ARMS 300 M10 SS 316 (BENT) THESE ARMS SUIT THE COFFIN STYLE TROUGHS USED BY FARMERS WITH SHEEP. FLOAT IS ATTACHED DIRECTLY TO THE ARM UNDER THE TROUGH COVER	 9 338862 000663
	0687	ARMS 150 M10 SS 316. THESE ARMS WERE DEVELOPED FOR BOTH ROUND PLASTIC TROUGHS AS WELL AS THE "CUP AND SAUCER" STYLE TANKS.	 9 338862 000687











	<p>0717</p>	<p>300MM M10 SS316 STRAIGHT (BOTTOM FILL TROUGHS) THESE ARMS ARE FOR FEEDLOT TROUGHS. THE INLET IS IN THE BOTTOM FACE OF THE TROUGH. THE VALVE IS INSTALLED VERTICALLY.</p>	 9 338862 000717
	<p>0724</p>	<p>ARMS 600 M10 SS316 (BENT). THESE ARMS WERE DEVELOPED FOR TANK INSTALLS. LARGE INFILL VALVES. THE FLOAT <u>SHOULD BE</u> ATTACHED TO THE ARM USING A SHORT KIT.</p>	 9 338862 000724

FLOAT ADAPTOR KITS

Stainless Chain Float kits.

These float kits come in two lengths 300mm and 600mm. The standard float kits come with metric M10 threaded nipples that suit our floats. A very limited number of 300mm chains with other nipples are available allowing our customers to fit alternate floats to our valves. The kits come with the following nipples: 5/16" BSW, 1/2" BSW but we will not be continuing to hold this stock moving forward.









Please note all Cocky Floats have a Metric M10 Threaded Brass bush inserted into the float during manufacture. If using a standard Cocky Float, then a standard Float Kit with an M10 nipple is required. These are highlighted below in yellow.

	CODE	DESCRIPTION	BARCODE
	0229	FLOAT ADAPTOR KIT (300MM SS 316 CHAIN WITH D SHACKLE & M10 NIPPLE) (SUITS COCKY FLOATS)	 9 338862 000229
	0236	FLOAT ADAPTOR KIT (300MM SS 316 CHAIN WITH D SHACKLE & 5/16" NIPPLE)	 9 338862 000236
	0250	FLOAT ADAPTOR KIT (300MM SS 316 CHAIN WITH D SHACKLE & 1/2" NIPPLE)	 9 338862 000250
	0571	FLOAT ADAPTOR KIT (600MM SS 316 CHAIN WITH D SHACKLE & M10 NIPPLE) (SUITS COCKY FLOATS)	 9 338862 000571
	0298	SHORT FLOAT KIT (2 x SS 316 M5 "D" SHACKLES WITH 1 x M10 NIPPLES) (SUITS COCKY FLOATS)	 9 338862 000298
	0335	SS 316 M5 "D" SHACKLE	 9 338862 000335

FLOATS

Cocky Ball Floats.





We supply our own range of ball floats specifically to suit our product range. Each float is clearly marked with its size 150mm (6"), 200mm (8"), 250mm (10") and the largest in our range the 300mm (12"). All Cocky Floats come in Safety Orange for easy checking even from a distance. The floats all have brass inserts with standard M10 threads. We regard our floats as the toughest and most reliable float on the market and they come with a **full replacement warranty** if used under normal operating conditions.

	CODE	DESCRIPTION	BARCODE
	0342	150MM (6") PLASTIC BALL FLOAT – HEAVY DUTY WITH 10MM BRASS INSERT	 9 338862 000342
	0359	200MM (8") PLASTIC BALL FLOAT – HEAVY DUTY WITH 10MM BRASS INSERT	 9 338862 000359
	0366	250MM (10") PLASTIC BALL FLOAT – HEAVY DUTY WITH 10MM BRASS INSERT	 9 338862 000366
	0373	300MM (12") PLASTIC BALL FLOAT – HEAVY DUTY WITH 10MM BRASS INSERT	 9 338862 000373
	0700	200MM SS 316 BALL FLOAT (8") THESE FLOATS ARE USED EXTENSIVELY IN THE FOOD INDUSTRY, HIGH TEMP INSTALLS AND CRITICAL INFRASTRUCTURE SUCH AS COOLING TOWERS. THE FLOAT HAS A BLIND HOLE THEREFORE PREVENTING ANY FLUID FROM ENTERING THE FLOAT. STRONG / RELIABLE.	 9 338862 000700

DEFLECTOR GUARDS

Splash Guards.

We produce a series of Stainless Steel splash guards for situations where our valves are installed above the water line. These guards are attached to the valve body by heavy duty stainless steel hose clamps and deflect the water down into the trough. They can be retrofitted to existing valves without having to remove the valve body. Made from Stainless Steel they will last a lifetime. Available to suit all valve sizes.

	CODE	DESCRIPTION	BARCODE
	00113	SS DEFLECTOR GUARDS TO SUIT 3/4" (19MM) & 1" (25MM) VALVE BODY	 9 338862 000113
	00120	SS DEFLECTOR GUARDS TO SUIT 1 1/4" (32MM) & 1 1/2" (38MM) VALVE BODY	 9 338862 000120
	00151	SS DEFLECTOR GUARDS TO SUIT 2" (50MM) VALVE BODY	 9 338862 000151




FLOAT ADAPTORS

Stainless steel SS316 Adapters.

We make a range of stainless steel adapters allowing our customers to fit virtually any combination of arm and float. Our Adapters come in the following sizes:

1. M10 internal to 5/16" BSW external.
2. M10 internal to 1/2" BSW external.

Please note all Cocky Floats have a Metric M10 Brass bush inserted into the float during manufacture. If using a standard Cocky Float arm there will be no need for an adapter.

	CODE	DESCRIPTION	BARCODE
	A0199	M10 - 5/16" BSW SS 316 ADAPTER	 9 338862 000199
	A0212	M10 - 1/2" BSW SS 316 ADAPTER	 9 338862 000212













SPARE PARTS

Spare Parts.

We provide our customers with a complete set of spare parts. Whether it's a washer, spare push rod or even a set of split pins. All spare parts come blister packed and bar coded for ease of ordering.

High Calcite Installations

The cocky valve is the only valve on the market in Australia to develop a method of combating excessive mineral build up in high calcite water. The cocky valve provides our customers with the option to fit a push rod made from Vesconite. These pushrods are self lubricating and resist the build up of minerals. We have had exceptional results with these pushrods and recommend them in any installation where high mineral content is present in the water.

	CODE	DESCRIPTION	BARCODE
	0304	Nitrile Replacement Washer 19mm (3/4") & 25mm (1") Valves	 9 338862 000304
	0311	NITRILE REPLACEMENT WASHER FOR 32MM (1 1/4") & 38MM (1 1/2") VALVES	 9 338862 000311
	0328	NITRILE REPLACEMENT WASHER FOR 50MM (2") VALVES	 9 338862 000328
	0397	GRADE SS 316 PUSHROD FOR 19MM (3/4") & 25MM (1") VALVES (STANDARD REPLACEMENT)	 9 338862 000397
	0403	GRADE SS 316 PUSHRODS FOR 32MM (1 1/4") & 38MM (1 1/2") & 50MM (2") VALVES. (STANDARD REPLACEMENT)	 9 338862 000403
	0137	VESCONITE PUSHRODS FOR 19MM (3/4") & 25MM (1") VALVES (FOR HIGH MINERAL CONTENT WATER)	 9 338862 000137
	0144	VESCONITE PUSHRODS FOR 32MM (1 1/4") & 38MM (1 1/2") & 50MM (2") VALVES. (FOR HIGH MINERAL CONTENT WATER)	 9 338862 000144
	0533	SET OF 2 GRADE SS 316 SPLIT PINS M5 x 32 (SUITS ALL VALVE SIZES.)	 9 338862 000533

	0502	CURRENT STYLE GRADE SS 316 WASHER SEAT FOR 3/4"(19MM) & 1" (25MM) VALVES	 9 338862 000502
	0519	CURRENT STYLE GRADE SS 316 WASHER SEAT FOR 1 1/4" (32MM) & 1 1/2" (38MM) VALVES	 9 338862 000519
	0526	CURRENT STYLE GRADE SS 316 WASHER SEAT FOR 2" (50MM) VALVES	 9 338862 000526
	0168	<p style="text-align: center;">SS 316 TEE PIECE</p> THIS ITEM ENABLES TWO FLOATS TO BE FITTED TO THE ONE ARM. THESE CAN BE USED WHEN THE CAVITY IS TOO SMALL FOR A LARGER FLOAT OR FOR VALVES FITTED UNDER GRILLS IN FEEDLOT STYLE TROUGHS	 9 338862 000168



For any Further information please contact us at :

Cocky Valve
Ph 1300 COCKYVALVE
Ph +61 3 9798 2633 Fax + 61 3 9798 2422

61 Macbeth St. Braeside. Vic 3195